



### Technical data FASTY Remote Rescue Vehicle

<b>FASTY Weight</b>	15 Kg
<b>FASTY Dimensions (LxWxH)</b>	115 cm x 80 cm x 25 cm
<b>FASTY Speed</b>	Maximum 15 km/h – Loaded 7.5 km/h
<b>FASTY Payload</b>	200 Kg – Maximum 2 persons
<b>FASTY Operating time</b>	60 Min. – Normal conditions
<b>FASTY Operating &amp; storage temperature</b>	-20 to +50 degrees Celsius
<b>FASTY Motors &amp; Energy</b>	DC Brushless, Battery Powered
<b>FASTY Frequency remote</b>	2.4 Ghz
<b>FASTY Safety and security</b>	– 2 flashing lights (red & green) – Shock absorber/impact absorber
<b>FASTY Equipment</b>	– Bracket for cameras – 4 handles and fasteners
<b>FASTY Case</b>	Impact-protected and with wheels
<b>FASTY Device colors</b>	Various colors on special order
<b>FASTY Optional</b>	– Manual control (forward / left, right) – Voice transmission (300 meters) – Protective covers – Device holder/mounting – Anti-slip pads – Reflectors – illumination – Autopilot

### Technical data FASTY Remote Controller

<b>RC – Weight</b>	342 g
<b>RC – Dimensions (LxWxH)</b>	21.3 cm x 11.7 cm x 11.6 cm
<b>RC – Transmission distance</b>	800 Meter
<b>RC – Frequency</b>	2.4 Ghz
<b>RC – Batteries / Accumulators</b>	6 x AA (commercially available)
<b>RC – Operating &amp; storage temperature</b>	-20 to +50 degrees Celsius
<b>RC – Telemetry</b>	FASTY signal quality and charge level indicator

### Technical data FASTY Battery / Battery

BATTERY – Typ	Li-ION
BATTERY –Capacity	600 Wh
BATTERY –Weight	4 Kg
BATTERY –Safety and Security	Overheating & Undervoltage
BATTERY –Charging time	4 hours

### Technical data FASTY Charger / Charging device

CHARGER – Charging voltage	25.2 Volts maximum
CHARGER – Charging current	3 Amps maximum
CHARGER – Operating temperature	-30 to +45 degrees Celsius
CHARGER – Storage temperature	-30 to +45 degrees Celsius

